

## ***Strictly Follow Owner's Manual While Operating This Unit***

### **Parts List: 6500T, 8000T**

#### **Deck Mounting**

- Pulley Casting with sheave installed (**#1**).
- One of 4", or 4-1/2", anodized aluminum tube – 90" long for Boom (**#2**)
- Davit Body Casting with winch installed (**#3**).
- One of 3-1/2", or 4" anodized aluminum tube – 48" long for upper standpipe (**#4**).
- Upper deck bushing casting (**#5**) with stainless steel pin (**#6**).
- Machined hardened Delrin bushings; for above deck (**#7**), and below deck (**#10**).
- Upper deck flange casting (**#8**).
- Lower deck flange casting (**#9**).
- One of 4", or 4 1/2" diameter anodized aluminum tube for lower standpipe (**#11**).
- One Universal Base Casting (**#12**) with Mounting Bolt.

#### *Available Options:*

- Remote Switch - To operate the crane's winch up to 8' away

#### **Transom Mounting**

- Pulley casting with sheave installed (**#1**).
- One of 4", or 4-1/2", anodized aluminum tube – 90" long for Boom (**#5**)
- Davit body with winch installed (**#6**).
- One of 3-1/2", or 4" anodized aluminum tube – 48" long for upper standpipe (**#4**).
- Drum Casting (**#19, 20A**)
- Machined hardened Delrin bushings; for above deck (**#7**), and below deck (**#10**).
- One of 4", or 4 1/2" diameter anodized aluminum tube for lower standpipe (**#11**).
- Universal Base Casting (**#12**) with Mounting Bolt.
- Adjustable "B-Arm" casting (splined) (**#21**), with Upper Flange Casting (**#7A**) connected
- Universal Base for deck or transom (splined) 6" x 8" (**#22**)
- Stainless Steel Cylinder, Assembled (**#8**)

#### *Available Options:*

- Remote Switch - To operate the crane's winch up to 8' away (12V Electric model only)
- Triangulated support braces (**#23,24**)